

SERIES 22

STAINLESS STEEL BALL VALVE 1000 WOG - FULL PORT - NPT ENDS

Specifications:


- End Type: NPT female/female
- Pressure rating: 1000 WOG
- Temperature: -20°F to 420°F
- · Handle with Locking Device
- · Blow-out proof stem design
- · Body and end caps quality investment casting
- 100% tested air under water, at 100 PSI, open and closed positions


Dimensions (in.)

SIZE	Α	В	d	S	L	WEIGHT (lbs.)
1/4"	1.91	1.89	0.45	0.75	3.58	0.19
3/8"	1.91	1.89	0.49	0.83	3.58	0.19
1/2"	2.28	2.05	0.59	1.00	3.58	0.27
3/4"	2.59	2.40	0.79	1.22	4.37	0.39
1"	3.03	2.56	0.98	1.48	4.37	0.55
1-1/4"	3.54	3.11	1.26	1.83	6.06	1.01
1-1/2"	3.86	3.27	1.50	2.11	6.06	1.29
2"	4.76	3.82	1.97	2.60	7.56	2.42

Materials List

NO	PART NAME	MATERIAL	NO. PCS.
1	CAP	316SS	1
2	BODY	316SS	1
3	BALL	316SS	1
4	BALL SEAT	PTFE	2
5	JOINT GASKET	PTFE	1
6	STEM PACKING	PTFE	1
7	THRUST WASHER	PTFE	1
8	STEM	304SS	1
9	GLAND NUT	304SS	1
10	HANDLE	304SS	1
11	SPRING WASHER	304SS	1
12	STEM NUT	304SS	1
13	PLASTIC SLEEVE	PLASTIC	1





Triad Process Equipment, Inc. 4922

Technical Drive Milford MI 48381

248.685.9938

www.triadprocess.com

Copyright 2007, Triad Process Equipment Triad and Triad Process Equipment are registered trademarks. We reserve the right to make technical and or dimensional changes without prior notice.

Rev 01 31416