

SERIES 22SRH

BALL VALVE WITH SPRING RETURN HANDLE

2 PIECE - FULL PORT - THREADED ENDS - 1000 PSI - DIRECT MOUNT



Specifications:

- Two Piece Design
- Pyramidal Stem Design
- Pressure Rating: 1000 PSI
- Temperature: 0°F to 400°F
- Blow-out Proof Stem
- ISO 5211 Top Flange for Direct Mounting

Materials List

NO	PART NAME	MATERIAL	NO. PCS.
1	BODY	CF8M	1
2	END CAP	CF8M	1
3	BALL	SS316	1
4	SEAT	PTFE/RTFE	2
5	JOINT GASKET	PTFE	1
6	STEM SEAL	RTFE	1
7	STEM	SS316	1
8	STEM PACKING	PTFE	*
9	GLAND	SS304	1
10	LOCK SADDLE	SS304	1
11	STEM NUT	SS304	1
12	HANDLE	SS304	1 set
13	HANDLE SLEEVE	VINYL	1
14	STEM WASHER	SS304	1
15	BELLEVILLE WASHER	SS316	2
16	STEM PACKING	25%GLASS FIBER FILLED + PTFE	1
17	O-RING	VITON	1
18	NYLOK STEM NUT	SS304	1

* - FOR 1/4"-1/2" - 1 PC, 3/4"-2" - 2 PCS.

Dimensions (in.)

SIZE	ØC	B	C	H	L	ISO-5211
1/4"	0.45	7.68	6.30	2.31	2.56	F03/F04
3/8"	0.49	7.68	6.30	2.31	2.56	F03/F04
1/2"	0.59	7.68	6.30	2.31	2.56	F03/F04
3/4"	0.79	7.68	6.30	2.60	2.94	F03/F04
1"	0.98	7.68	6.30	3.02	3.46	F04/F05
1-1/4"	1.26	7.68	6.30	3.19	4.02	F04/F05
1-1/2"	1.50	10.43	8.27	3.84	4.33	F05/F07
2"	1.97	10.43	8.27	4.14	4.92	F05/F07

